NEW 2016

Recessed LED Stair Light and Wall Light

Stainless steel front cover with Matte Surface

LED Colour Temperature

- 2000K
- 3000K
- 6000K

Optics

- N/A

Outer Dimensions



Mounting sleeve 100#

Material specifications

Housing	12# Die-casting aluminum T=20-25μm.Adhesion of ISO class 1/ ASTM class 4B high temperature painting
Front cover	Hard chrome-plated stainless steel SUS 316#
Light Source	Emitter type power LED
LED Driver	Constant Voltage Input,Constant Current Output
Operating temperature	-20°C~40°C
Power Cable	H05RN-F 2X1.0mm² L=0.3m(low voltage)
Mounting sleeve	ABS 100#
Dimmable Surpport	**Triac PWM 1-10 Dali**

Lighting Effect demo & Installation



Wall recessed



Installation with clips embedded into sleeve,fix on the concrete wall

Installation with clips directly

Item	Light source	Lens	The manufacturer selected lens degree(°)θ1/2	Input voltage(v)	Typical operating current(mA)	Typical consumption(w)	Typical luminance(lm)	IK rate
B1AAR0102	1×2W	L0180C010AR	50°	24V DC	100	2.4	Cool white =40 Warm white =36	10











Recessed LED Stair Light and Wall Light

Stainless steel front cover with Matte Surface

LED Colour Temperature

- 2000K
- 3000K
- 6000K

Optics

- N/A

NEW 2016

Outer Dimensions



Mounting sleeve 100#

Material specifications

Housing	12# Die-casting aluminum T=20-25μm.Adhesion of ISO class 1/ ASTM class 4B high temperature painting
Front cover	Hard chrome-plated stainless steel SUS 316#
Light Source	Emitter type power LED
LED Driver	Constant Voltage Input,Constant Current Output
Operating temperature	-20°C~40°C
Power Cable	H05RN-F 2X1.0mm² L=0.3m(low voltage)
Mounting sleeve	ABS 100#
Dimmable Surpport	**Triac PWM 1-10 Dali**

Lighting Effect demo & Installation



Wall recessed



Installation with clips embedded into sleeve,fix on the concrete wall

Installation with clips directly

Item	Light source	Lens	The manufacturer selected lens degree(°)θ1/2	Input voltage(v)	Typical operating current(mA)	Typical consumption(w)	Typical luminance(lm)	IK rate
B1AAS0102	1×2W	L0180C010AR	50°	24V DC	100	2.4	Cool white =54 Warm white =49	10