




Central Ejective Fountain Light

Completely Hard chromeplated Stainless Steel SUS 316L# Housing and Accessory




Outer Dimensions




Warning:
Must be installed under the water to prevent the light from burning up because of over-heating.

Material specifications

Housing	Hard chromeplated molding shaped stainless steel SUS 316L#
Light Window	Step tempered glass, 10mm
Gasket	Silicone gasket
Cable gland	IP-68 PG-11 copper with nickel-coated
PCB	Excellent heat conductivity aluminum, coefficient of heat Conductivity 2.0w/mk
LED Driver	Constant Voltage Input, Constant Current Output
Power Cable	H07RN-F 2X1.0mm² L=3.0m
Application environment	Temperature of water between -20°C~40°C less than 1 meter depth.
Dimmable Support	Triac PWM 1-10 Dali



Central Ejective



Water jet pipe G1 1/2" taper



LED Colour Temperature


- 2000K
- 3000K
- 6000K

Optics



B32
L0120F024PS 20°
L0125F024PS 25°
L0130F024PS 30°
L0135F024PS 35°

B32



20° 25° 30° 35° 45°

Item	Light source	Lens	The manufacturer selected lens degree(°)	Input voltage(V)	Typical operating current(mA)	Typical consumption(W)	Typical luminance(lm)	IK rate
B4TA1257	12x2W	B32	25°	24V DC	1200	28.8	Cool white=2047 Warm white=1610	09

