

NEW 2016



RGB LED Underwater Spot Light

LED Wave Length

- R =620-630 nm
- G =520-530 nm
- B =460-470 nm

Optics




B34D



30°

Outer Dimensions




5002
Tripod-Optional Accessory





Material specifications

Front cover&Housing	Hard chromeplated Molding shaped stainless steel SUS 316L*
PMMA	13mm
Gasket	EPDM gasket
LED	Nichia
Cable gland	IP-68 PG-11 copper with nickel-coated
PCB	Excellent heat conductivity aluminum, coefficient of heat conductivity22.0w/mk
LED Driver	Constant Voltage Input.Constant Current Output
Power Cable	H07RN-F 4X1.0mm2 L=3.0m
Application environment	Temperature of water between -20°C~40°C less than 1 meter depth.

Warning:
Must be installed under the water to prevent the light from being burnt off because of over-heating.



Item	Light source	Lens	The manufacturer selected lens degree(°)B1/2	Input voltage(V)	Typical operating current(mA)	Typical consumption(W)	Typical luminance(lm)	IK rate
B5YA0603	6×2W RGB 3IN1 6R/6G/6B	B34D	30°	24V DC	640	15.4	516	10



382



RGB LED Underwater Spot Light

LED Wave Length

- R =620-630 nm
- G =520-530 nm
- B =460-470 nm

Optics




B34D



30°

Outer Dimensions



5003
Tripod-Optional Accessory





Material specifications

Front cover&Housing	Hard chromeplated Molding shaped stainless steel SUS 316L*
PMMA	13mm
Gasket	EPDM gasket
LED	Nichia
Cable gland	IP-68 PG-11 copper with nickel-coated
PCB	Excellent heat conductivity aluminum, coefficient of heat conductivity22.0w/mk
LED Driver	Constant Voltage Input.Constant Current Output
Power Cable	H07RN-F 4X1.0mm2 L=3.0m
Application environment	Temperature of water between -20°C~40°C less than 1 meter depth.

Warning:
Must be installed under the water to prevent the light from being burnt off because of over-heating.



Item	Light source	Lens	The manufacturer selected lens degree(°)B1/2	Input voltage(V)	Typical operating current(mA)	Typical consumption(W)	Typical luminance(lm)	IK rate
B5ZA0604	6×2W RGB 3IN1 6R/6G/6B	B34D	30°	24V DC	994	24	703	10



383