NEW 2016

Diffused Beam

Recessed LED Wall Light

Stainless steel front cover with Matte Surface

Outer Dimensions

Mounting sleeve 091#

Material specifications

Housing	12# Die-casting grey powder coated aluminum. T=60-80um Adhesion of ISO class 1/ASTM class 48
Front cover	Hard chromeplated Stainless steel 316#
LED	**SMD3030** type LED
Cable gland	IP-67 copper and nicked coated
Gasket	Molding shaped silicone seal
LED Driver	Constant Voltage Input,Constant Current Output
Operating temperature	-20˚C~40˚C
Power Cable	H05RN-F 2X1.0mm² L=0.5m (low voltage) H05RN-F 3X1.0mm² L=0.5m (high voltage)
Mounting sleeve	ABS 091#
Dimmable Support	**Triac PWM 1-10 Dali**

Item	Light source	Input voltage(v)	Typical operating current(mA)	Typical consumption(w)	Typical luminance(lm)	IK rate
D1FC3634	36x0.1W	24V DC 120/240	24V =235 120V=99 240V=55	24V =5.5 120V=6.7 240V=6.5	Cool white =113 Warm white =98.9	09









NEW 2016

Recessed LED Stair Light and Wall Light

Outer Dimensions

Unit:mm



Mounting sleeve 092#

Material specifications

Housing	12# Die-casting grey powder coated aluminum. T=60-80um Adhesion of ISO class 1/ASTM class 48
Front cover	12# Die-casting aluminum **RAL7037** powder coated T=60-80μm.Adhesion of ISO class 1/ASTM class 48;
LED	**SMD3030** type LED
Cable gland	IP-67 copper and nicked coated
Gasket	Molding shaped silicone seal
LED Driver	Constant Voltage Input,Constant Current Output
Operating temperature	-20˚C~40˚C
Power Cable	H05RN-F 2X1.0mm² L=0.5m (low voltage) H05RN-F 3X1.0mm² L=0.5m (high voltage)
Mounting sleeve	ABS 092#
Dimmable Support	**Triac PWM 1-10 Dali**

Front Cover Color Option

Basic	Secondary	
Dark Grey RAL 7037	Light Sanded Grey RAL 7038	Sanded Black RAL9005

Item	Light source	Input voltage(v)	Typical operating current(mA)	Typical consumption(w)	Typical luminance(lm)	IK rate
D1HA1034	10×0.5W	24V DC 120/240	24V = 230 120V = 105 240V = 58	24V = 5.5 120V = 7.3 240V = 7.4	Cool white =124.6 Warm white =112.9	10