











GROUND LIGHTS

COLOR : BF ■ LED COLOR : WW ■ NW ■

GA-224Q		  IP67		 3000	 DRIVER Build-in																																																
 ErP Class A			LED / Pieces OSRAM / 4pcs																																																		
			POWER 1.2Wx4 (350mA)																																																		
			INPUT AC 100 - 240V																																																		
OSLON 4pcs(350mA) WW 8° <table><tr><th>H(m)</th><th>D(m)</th><th>E(lx)</th></tr><tr><td>1.0</td><td>0.1</td><td>6570</td></tr><tr><td>2.0</td><td>0.3</td><td>1643</td></tr><tr><td>3.0</td><td>0.4</td><td>730</td></tr></table> OSLON 4pcs(350mA) WW 12° <table><tr><th>H(m)</th><th>D(m)</th><th>E(lx)</th></tr><tr><td>1.0</td><td>0.2</td><td>2690</td></tr><tr><td>2.0</td><td>0.4</td><td>673</td></tr><tr><td>3.0</td><td>0.6</td><td>299</td></tr></table> OSLON 4pcs(350mA) WW 24° <table><tr><th>H(m)</th><th>D(m)</th><th>E(lx)</th></tr><tr><td>1.0</td><td>0.4</td><td>1140</td></tr><tr><td>2.0</td><td>0.9</td><td>285</td></tr><tr><td>3.0</td><td>1.3</td><td>127</td></tr></table> OSLON 4pcs(350mA) WW 36° <table><tr><th>H(m)</th><th>D(m)</th><th>E(lx)</th></tr><tr><td>1.0</td><td>0.6</td><td>790</td></tr><tr><td>2.0</td><td>1.3</td><td>198</td></tr><tr><td>3.0</td><td>1.9</td><td>88</td></tr></table>						H(m)	D(m)	E(lx)	1.0	0.1	6570	2.0	0.3	1643	3.0	0.4	730	H(m)	D(m)	E(lx)	1.0	0.2	2690	2.0	0.4	673	3.0	0.6	299	H(m)	D(m)	E(lx)	1.0	0.4	1140	2.0	0.9	285	3.0	1.3	127	H(m)	D(m)	E(lx)	1.0	0.6	790	2.0	1.3	198	3.0	1.9	88
H(m)	D(m)	E(lx)																																																			
1.0	0.1	6570																																																			
2.0	0.3	1643																																																			
3.0	0.4	730																																																			
H(m)	D(m)	E(lx)																																																			
1.0	0.2	2690																																																			
2.0	0.4	673																																																			
3.0	0.6	299																																																			
H(m)	D(m)	E(lx)																																																			
1.0	0.4	1140																																																			
2.0	0.9	285																																																			
3.0	1.3	127																																																			
H(m)	D(m)	E(lx)																																																			
1.0	0.6	790																																																			
2.0	1.3	198																																																			
3.0	1.9	88																																																			
GA-207Q		  IP67		 3000	 DRIVER Build-in																																																
 ErP Class A			LED / Pieces OSRAM / 7pcs																																																		
			POWER 1.2Wx7 (350mA)																																																		
			INPUT AC 100 - 240V																																																		
OSLON 7pcs(350mA) WW 12° <table><tr><th>H(m)</th><th>D(m)</th><th>E(lx)</th></tr><tr><td>1.0</td><td>0.2</td><td>7650</td></tr><tr><td>2.0</td><td>0.4</td><td>1913</td></tr><tr><td>3.0</td><td>0.6</td><td>850</td></tr></table> OSLON 7pcs(350mA) WW 20° <table><tr><th>H(m)</th><th>D(m)</th><th>E(lx)</th></tr><tr><td>1.0</td><td>0.4</td><td>2750</td></tr><tr><td>2.0</td><td>0.7</td><td>688</td></tr><tr><td>3.0</td><td>1.1</td><td>306</td></tr></table> OSLON 7pcs(350mA) WW 30° <table><tr><th>H(m)</th><th>D(m)</th><th>E(lx)</th></tr><tr><td>1.0</td><td>0.5</td><td>1300</td></tr><tr><td>2.0</td><td>1.1</td><td>325</td></tr><tr><td>3.0</td><td>1.6</td><td>144</td></tr></table> OSLON 7pcs(350mA) WW 60° <table><tr><th>H(m)</th><th>D(m)</th><th>E(lx)</th></tr><tr><td>1.0</td><td>1.2</td><td>800</td></tr><tr><td>2.0</td><td>2.3</td><td>200</td></tr><tr><td>3.0</td><td>3.5</td><td>89</td></tr></table>						H(m)	D(m)	E(lx)	1.0	0.2	7650	2.0	0.4	1913	3.0	0.6	850	H(m)	D(m)	E(lx)	1.0	0.4	2750	2.0	0.7	688	3.0	1.1	306	H(m)	D(m)	E(lx)	1.0	0.5	1300	2.0	1.1	325	3.0	1.6	144	H(m)	D(m)	E(lx)	1.0	1.2	800	2.0	2.3	200	3.0	3.5	89
H(m)	D(m)	E(lx)																																																			
1.0	0.2	7650																																																			
2.0	0.4	1913																																																			
3.0	0.6	850																																																			
H(m)	D(m)	E(lx)																																																			
1.0	0.4	2750																																																			
2.0	0.7	688																																																			
3.0	1.1	306																																																			
H(m)	D(m)	E(lx)																																																			
1.0	0.5	1300																																																			
2.0	1.1	325																																																			
3.0	1.6	144																																																			
H(m)	D(m)	E(lx)																																																			
1.0	1.2	800																																																			
2.0	2.3	200																																																			
3.0	3.5	89																																																			

OPTIONAL ACCESSORIES FOR GA-207



Honeycomb AC-217



Sculptured Lens AC-207