


CEILING LIGHTS

COLOR : WU BJ SY LED COLOR : WW NW





450lm




DG-F02-24V IP44 on the front.

LED	POWER	LED COLOR	COLOR
SHARP	4.8W(200mA, 24V)	<input type="checkbox"/> WW <input type="checkbox"/> NW	<input type="checkbox"/> WK <input type="checkbox"/> BJ <input type="checkbox"/> SY

Housing: aluminium, paint.





450lm



DG-F02D-24V

LED	POWER	LED COLOR	COLOR
SHARP	4.8W(200mA, 24V)	<input type="checkbox"/> WW <input type="checkbox"/> NW	<input type="checkbox"/> WK <input type="checkbox"/> BJ <input type="checkbox"/> SY

Housing: aluminium, paint, 270°rotating & 15°tilting.



PARALLEL CONNECTOR FOR 3, 6 OR 8 LUMINAIRES

Model	Quick connectors	Numbers of luminaires	Driver diagram
LDL-AC2-3P		up to 3	
LDL-AC2-6P		up to 6	

Driver	Quantity of DG-F02D-24V
LMV12W24 UNI (4.8W/9.6W)	1 ~ 2 pcs
LLV20W24 UNI (14.4W/19.2W)	3-4 pcs
EIP030V0240U1 (24W/28.8W)	5-6 pcs

*For constant voltage use only.